Panamich

TECHNOLOGY CHANGE TO LIFE

NAN TOUCH *MicroTouch*®

Panamich(Shang Hai) Electronic Co.,Ltd

http://www.nyantouch.com
http://www.gonsion.com
http://www.panamich.com

01.01.2020

Panamich

Panamich electronic is a manufacturer of innovative display touch system solutions for customers all over the world. The company has many years of experience in touch and LCD module design and manufacturing team. With excellent operation mode of in-depth technology development and design integration, Panamich electronics provides a full range of touch display technology solutions.

We will continue to develop advanced touch and integration technologies, lay out the thinnest and narrowest borders, giant size and 3D appearance technologies in the industry, and integrate the touch display solutions with the most complete technical level and service in the industry. To pursue higher profits and value as the goal, steady growth. For the retail, entertainment, medical, automotive, industrial, exhibition and game application market customers to develop solutions and new application products closer to market demand, to a greater extent to meet the needs of customers in various industries, and to create maximum value for customers.

In the future, we will continue to streng then the competitive advantage of differentiation through the diversified integration of cross domain, extensible and multi application, as well as the differentiated business model with high added value.

Open Frame Multi-Touch Display

- Using Projection Capacitive Screen Technology (PCAP)
- Ultra-fast 5 ms touch response for quick interactions
- Anti-stiction surface enhances the user experience
- Provides 91% light transmission
- Siz: 10"-32" （Can be customized according to customer requirements）

Suggested Applications

- Upscale Department
- Stores
- Sample Applications
- Wayfinding/
- Information
- Endless Aisle
- Educational Exhibits
- Entertainment
- Assisted Selling

- Public Venues
- Shopping Malls
- Museums
- Event Centers
- Campuses
- Branded Retail
- Automotive
- Showrooms
- Luxury Retail
- Fashion

✔ Fully-Integrated Chassis Solution
✔ Exceptional Touch Performance
✔ Robust, Durable and Dependable
✔ Consumer-Driven Design
✔ Stable Life-Cycle Product Availability

Installation method

Open Frame Multi-Touch Display Specifications

Diagonal Size	10.4"	12.1"	15.6"	17"	18.5"	21.5"	24"	27"	32"
Part Number	98-1001-225-01	98-1200-225-01	98-1500-225-01	98-1700-225-01	98-1850-225-01	98-0003-4242-2	98-2390-225-01	98-2700-225-01	98-3239-225-01
Model	C1001PW	C1200PW	C1500PW	C1700PW	C1867PW	C2167PW	C2467PW	C2767PW	C3239PW
Number of Touch Points	10 points	10 points	10 points	10 points	10 points	10 points	10 points	10 points	10 points
Aspect Ratio	4：3	4：3	4：3 / 16:9	5：4	16：9	16：9	16：9	16：9	16：9
Touch Response Time*	<8ms	<8ms	<8ms	<8ms	<8ms	<8ms	<8ms	<8ms	<8ms
Display Resolution	800*600	1024*768	1024*768 / 1920*1080	1280*1024	1366*768 / 1920*1080	1920*1080	1920*1080	1920*1080 / 3840*2160	1920*1080 / 3840*2160
Display Colors	16.7M/262K colors	16.7M/262K colors	16.2M colors	16.7M colors	16.7M colors	16.7M colors	16.7M colors	16.7M colors	16.7M colors
Pixel Pitch	0.264mm x 0.264mm	0.24mm x 0.24mm	0.297 X 0.297mm	0.264mm x 0.264mm	213（per one triad）213	248.25(per one triad)248.25	274.5(per one triad)274.5	311.25(per one triad)311.25	03637mm x 03637mm
Backlight	LED	LED	LED	LED	LED	LED	LED	LED	LED
Contrast Ratio	500：1	700：1	1000:1	1000：1	1000：1	3000:1	1000:1	3000;1	3000:1
Viewing Angle	150° (Vertical/Horizontal)	150° (Vertical/Horizontal)	178° (Vertical/Horizontal)	178° (Vertical/Horizontal)	178° (Vertical/Horizontal)	178° (Vertical/Horizontal)	178° (Vertical/Horizontal)	178° (Vertical/Horizontal)	178° (Vertical/Horizontal)
Brightness	350 Nit	500 Nit	250 Nit	250 Nit	350 Nit	300 Nit	250 Nit	350 Nit	450 Nit
Brightness with Touch	300 Nit	450 Nit	230 Nit	200 Nit	300 Nit	250 Nit	230 Nit	200 Nit	400 Nit
Multimedia	x	x	x	x	x	x	x	x	x
Surface Treatment	Anti-glare	Anti-glare	Anti-glare	Anti-glare	Anti-glare	Anti-glare	Anti-glare	Anti-glare	Anti-glare
Touch Communication	USB	USB	USB	USB	USB	USB	USB	USB	USB
Video Connections	VGA	VGA	VGA / HDMI	VGA / HDMI	VGA / HDMI	VGA / HDMI /Dvi	VGA / HDMI /Dvi	VGA / HDMI /Dvi	VGA / HDMI /Dvi
Power Supply	12V DC 90/240V AC	12V DC 90/240V AC	12V DC 90/240V AC	12V DC 90/240V AC	12V DC 90/240V AC	12V DC 90/240V AC	12V DC 90/240V AC	12V DC 90/240V AC	90/240V AC
Operating Systems Compatibility	Windows11/10/7/xp/Mac/Android/Kylin	Windows11/10/7/xp/Mac/Android/Kylin	Windows11/10/7/xp/Mac/Android/Kylin	Windows11/10/7/xp/Mac/Android/Kylin	Windows11/10/7/xp/Mac/Android/Kylin	Windows11/10/7/xp/Mac/Android/Kylin	Windows11/10/7/xp/Mac/Android/Kylin	Windows11/10/7/xp/Mac/Android/Kylin	Windows11/10/7/xp/Mac/Android/Kylin
Warranty	One Year	One Year	One Year	One Year	One Year	One Year	One Year	One Year	One Year
Operating Environment	-10°-50° Relative Humidity, Non-condensing 85%	-10°-50° Relative Humidity, Non-condensing 85%	-10°-50° Relative Humidity, Non-condensing 85%	-10°-50°Relative Humidity, Non-condensing 85%	-10°-50° Relative Humidity, Non-condensing 85%	-10°-50° Relative Humidity, Non-condensing 85%	-10°-50° Relative Humidity, Non-condensing 85%	-10°-50° Relative Humidity, Non-condensing 85%	-10°-50° Relative Humidity, Non-condensing 85%
Storage Environment	-10°-50°	-10°-50°	-10°-50°	0°-50°	-10°-50°	-10°-50°	-10°-50°	-10°-50°	-10°-50°

The above installation methods are for reference only.

Recommended Applications

• Public Venues • Shopping Malls • Museums • Event Centers • Campuses • Branded Retail • Automotive • Showrooms • Luxury Retail • Fashion

• Upscale Department • Stores • Sample Applications • Wayfinding/ • Information • Endless Aisle • Educational Exhibits • Entertainment • Assisted Selling